## **Technical Report Documentation Page**

reclinical Report Documentation Fage					
1. Report No. FHWA/NC/2006-45	2. Govern	ment Accession No.	3.	Recipient's Cata	alog No.
4. Title and Subtitle Signal Replacement with an Interchange			5. Report Date August 24, 2007		
			6.	Performing Org	anization Code
7. Author(s): Martin R. Kane, Caroline M. Kone, William Andrew Eagle			8. Performing Organization Report No.		
9. Performing Organization Name and Address Department of Civil & Environmental Engineeri University of North Carolina at Charlotte Charlotte, North Carolina 28223-0001		ing		Work Unit No. (	
			11. Contract or Grant No.		
12. Sponsoring Agency Name and Address North Carolina Department of Transportation Research and Analysis Group 1 South Wilmington Street Raleigh, North Carolina 27601				Type of Report  Final Report  July 2005 - Ma	and Period Covered arch 2007
				Sponsoring Age 2006-11	ency Code
Supplementary Notes:					
The purpose of this research effort is to evaluate unique intersection designs for their suitability for use in lieu of an existing or proposed traffic signal. Traffic signals can cause unnecessary delay and capacity restrictions due to the operational characteristics of signalized intersections. This project identified alternative intersection (interchange) designs that could be implemented at signalized intersections that would serve the current traffic and also provide a higher capacity for the main traffic movement. Analyses were conducted primarily using SYNCHRO 6 software from Trafficware Ltd. To model the different intersection/interchange designs identified for analysis. Eight designs were selected for in-depth analysis: Continuous Flow, Center —Turn Overpass, Echelon, Median U-turn, Michigan Diamond, Quadrant, SPUI, and Tight Diamond. While the Tight Diamond performed very well in the simulation, the consensus of experienced traffic engineers (Thrower, Naylor, et al.) was that there were errors in the simulation that resulted in much better than expected results. Further analysis will be conducted on this design, not related to this project, to see if the problem can be identified. Because of the lack of confidence in the Tight Diamond results, the Tight Diamond will not be included in the recommendations. When the different designs were evaluated at selected locations in different areas of the state, the lower cost designs usually prevailed based on predicted traffic levels and construction costs. The evaluated designs did indicate a significant increase in capacity when compared to a "regular" signalized intersection.					
17. Key Words Unconventional Intersection Designs; Alte designs for signalized intersections; Center Overpass; Continuous Flow Intersection; Floring Intersection; Quadrant Intersection; Michig Diamond Intersection; Median U-turn Inter Single Point Urban Interchange; SPUI; Ru Signalized intersections; High-capacity intersections	18. Distribution Statement				
19. Security Class if. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified		21. N	No. of Pages 170	22. Price